

SECTION 1 IDENTIFICATION

Product Name: Signature® HD SB MO 10W-30 and 15W-40

Distributor Information:

Parman Energy Group 7101 Cockrill Bend Blvd Nashville, TN 37209 (800) 727-7920

Product Use: Diesel Engine Oil

Emergency Phone Number:

PERS (800) 633-8253

SECTION 2 HAZARD(S) IDENTIFICATION

Classification: Not classified as hazardous according to 29 CFR 1910.1200 (2012).

Environmental Hazards: Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary Statements:

Prevention: Avoid release to the environment.

Disposal: Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Hazards Not Otherwise Classified: Not Applicable

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Amount
Highly Refined Mineral Oil (C15-C50)	Mixture	70-99 % weight

SECTION 4 FIRST-AID MEASURES

Description of first aid measures

Eye: No specific first aid measures are required. As a precaution, remove contact lenses, if worn, and flush eyes with water.

Skin: No specific first aid measures are required. As a precaution, remove clothing and shoes if contaminated. To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

Ingestion: No specific first aid measures are required. Do not induce vomiting. As a precaution, get medical advice.

Product (s) manufactured in the USA.



Inhalation: No specific first aid measures are required. If exposed to excessive levels of material in the air, move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs.

Most important symptoms and effects, both acute and delayed

IMMEDIATE HEALTH EFFECTS

Eye: Not expected to cause prolonged or significant eye irritation.

Skin: Contact with the skin is not expected to cause prolonged or significant irritation. Contact with the skin is not expected to cause an allergic skin response. Not expected to be harmful to internal organs if absorbed through the skin. **Ingestion:** Not expected to be harmful if swallowed.

Inhalation: Not expected to be harmful if inhaled. Contains a petroleum-based mineral oil. May cause respiratory irritation or other pulmonary effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended mineral oil mist exposure limit. Symptoms of respiratory irritation may include coughing and difficulty breathing.

DELAYED OR OTHER HEALTH EFFECTS: Not classified

Indication of any immediate medical attention and special treatment needed Not Applicable

SECTION 5 FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable: Use water, fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

Protection for Fire Fighters:

Fire-Fighting Instructions: This material will burn although it is not easily ignited. See Section 7 for proper handling and storage. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including selfcontained breathing apparatus.

Combustion Products: Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Protective Measures: Eliminate all sources of ignition in vicinity of spilled material.

Spill Management: Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations.

Reporting: Report spills to local authorities and/or the U.S. Coast Guard's National Response Center at (800) 424-8802 as appropriate or required.

Product (s) manufactured in the USA.



SECTION 7 HANDLING AND STORAGE

General Handling Information: Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

Precautionary Measures: Keep out of the reach of children.

Static hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures.

Container Warnings: Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressur ize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioned or disposed of properly.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

General Considerations:

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Engineering Controls: Use in a well-ventilated area.

Personal Protective Equipment:

Eye/Face Protection: No special eye protection is normally required. Where splashing is possible, wear safety glasses with side shields as a good safety practice.

Skin and Body Protection: No special protective clothing is normally required. Where splashing is possible, select protective clothing depending on operations conducted, physical requirements and other substances in the workplace. Suggested materials for protective gloves include: 4H (PE/EVAL), Nitrile Rubber, Silver Shield, Viton.

Respiratory Protection: No respiratory protection is normally required. If user operations generate an oil mist, determine if airborne concentrations are below the occupational exposure limit for mineral oil mist. If not, wear an approved respirator that provides adequate protection from the measured concentrations of this material. For air-purifying respirators use a particulate cartridge. Use a positive pressure air-supplying respirator in circumstances where air-purifying respirators may not provide adequate protection.

Occupational Exposure Limits:

Product (s) manufactured in the USA.



Component							
Highly refined mineral oil (C15-C50)	OSHA Z-1	TWA	STEL	Ceiling			
Highly refined mineral oil (C15-C50)	ACGIH	5 mg/m3					

Consult local authorities for appropriate values

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Attention: the data below are typical values and do not constitute a specification.

Color: Light to Brown
Physical State: Liquid
Odor: Petroleum odor

Odor Threshold: No data available pH:

No data available

Vapor Pressure: No data available

Vapor Density (Air = 1): No data available

Initial Boiling Point: 315°C (599°F)

Solubility: Soluble in hydrocarbon; insoluble in water.

Freezing Point: No data available Melting Point: No data available

Density: $0.8779 \text{ kg/l} @ 15^{\circ} \text{ C } (59^{\circ} \text{ F) } (\text{Typical})$

Viscosity: 14 mm2/s @ 100° C (212° F) Minimum Evaporation

Rate: No data available

Decomposition temperature: No data available

Octanol/Water Partition Coefficient: No data available

Flammable Properties:

Flammability (solid, gas): No data available

Flash Point: (Cleveland Open Cup) 215°C (419°F) Minimum Auto-ignition

temperature: No data available

Flammability (Explosive) Limits (% by volume in air): Lower: Not applicable Upper: Not applicable

SECTION 10 STABILITY AND REACTIVITY

Reactivity: May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

Chemical Stability: This material is considered stable under normal ambient and anticipated storage and handling conditions of

temperature and pressure.

Incompatibility With Other Materials: Not applicable

Product (s) manufactured in the USA.



Hazardous Decomposition Products: None known (None expected) Hazardous

Polymerization: Hazardous polymerization will not occur.

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects:

Serious Eye Damage/Irritation: The eye irritation hazard is based on evaluation of data for product components.

Skin Corrosion/Irritation: The skin irritation hazard is based on evaluation of data for product components.

Skin Sensitization: The skin sensitization hazard is based on evaluation of data for product components.

Acute Dermal Toxicity: The acute dermal toxicity hazard is based on evaluation of data for product components.

Acute Oral Toxicity: The acute oral toxicity hazard is based on evaluation of data for product components.

Acute Inhalation Toxicity: The acute inhalation toxicity hazard is based on evaluation of data for product components.

Acute Toxicity Estimate: Not determined.

Germ Cell Mutagenicity: The hazard evaluation is based on data for components or a similar material.

Carcinogenicity: The hazard evaluation is based on data for components or a similar material.

Reproductive Toxicity: The hazard evaluation is based on data for components or a similar material.

Specific Target Organ Toxicity – Single Exposure: The hazard evaluation is based on data for components or a similar material. **Specific Target Organ Toxicity – Repeated Exposure:** The hazard evaluation is based on data for components or a similar material.

Additional Toxicology Information:



During use in engines, contamination of oil with low levels of cancer-causing combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water. This product contains petroleum base oils which may be refined by various processes including severe solvent extraction, severe hydrocracking, or severe hydrotreating. None of the oils requires a cancer warning under the OSHA Hazard Communication Stand and (29 CFR 1910.1200). These oils have not been listed in the National Toxicology Program (NTP) Annual Report nor have they been classified by the International Agency for Research on Cancer (IARC) as; carcinogenic to humans (Group 1), probably carcinogenic to humans (Group 2A), or possibly carcinogenic to humans (Group 2B). These oils have not been classified by the American Conference of Governmental Industrial Hygienists (ACGIH) as: confirmed human carcinogen (A1), suspected human carcinogen (A2), or confirmed animal carcinogen with unknown relevance to humans (A3).

SECTION 12 ECOLOGICAL INFORMATION

Ecotoxicity:

This material is expected to be harmful to aquatic organisms and may cause long-term adverse effects in the aquatic environment. The product has not been tested. The statement has been derived from the properties of the individual components.

Mobility:

No data available.

Persistence and Degradability:

This material is not expected to be readily biodegradable. The biodegradability of this material is based on an evaluation of data for the components or a similar material. The product has not been tested. The statement has been derived from the properties of the individual components.

Potential to Bioaccumulate

Bioconcentration Factor: No data available

Octanol/Water Partition Coefficient: No data available

SECTION 13 DISPOSAL CONSIDERATIONS

Use material for its intended purpose or recycle if possible. Oil collection services are available for used oil recycling or disposal. Place contaminated materials in containers and dispose of in a manner consistent with applicable regulations. Contact your sales representative or local environmental or health authorities for approved disposal or recycling methods.

SECTION 14 TRANSPORT INFORMATION

The description shown may not apply to all shipping situations. Consult 49CFR, or appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

DOT Shipping Description: PETROLEUM LUBRICATING OIL, NOT REGULATED AS A HAZARDOUS MATERIAL FOR TRANSPORTATION UNDER 49 CFR

IMO/IMDG Shipping Description: PETROLEUM LUBRICATING OIL; NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER THE IMDG CODE

Product (s) manufactured in the USA.



ICAO/IATA Shipping Description: PETROLEUM LUBRICATING OIL; NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER ICAO TI OR IATA DGR

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code: Not applicable

SECTION 15 REGULATORY INFORMATION

1. Immediate (Acute) Health Effects: No

2. Delayed (Chronic) Health Effects: No

3. Fire Hazard: No

4. Sudden Release of Pressure Hazard: No

5. Reactivity Hazard: No

REGULATORY LISTS SEARCHED

01-1=IARC Group 1

01-2A=IARC Group 2A

01-2B=IARC Group 2B

02=NTP Carcinogen

EPCRA 311/312 CATEGORIES

03=EPCRA 313

04=CA Proposition 65

05=MA RTK 06=NJ RTK

07=PA RTK

No components of this material were found on the regulatory lists above.

Chemical Inventories:

All components comply with the following chemical inventory requirements: AICS (Australia), DSL (Canda), KECI (Korea), PICCS (Philippines), TSCA (United States).

One or more components is listed on ELINCS (European Union). Secondary notification by the importer may be required. All other components are listed or exempted from listing on EINECS.

One or more components does not comply with the following chemical inventory requirements: ENCS (Japan).

New Jersey RTK Classification:

SECTION 16 OTHER INFORMATION

Under the New Jersey Right-to-Know Act L. 1983 Chapter 315 N.J.S.A. 34:5A-1 et. Seq., the product is to be identified as follows: PETROLEUM OIL (Motor oil)

NFPA Ratings

NFPA Health Hazard 0 HMIS Rating

Product (s) manufactured in the USA.



NFPA Fire Hazard	1	HMIS Health Hazard	0 NFPA Reactivity	0		
HMIS Fire Hazard	1			HMIS Reactivity 0		
(O-Least, 1-Slight, 2-Mode Extreme, PPE:- Personal F Equipment Index recomm *Chronic Effect Indicator) obtained using the guidel evaluations prepared by the Protection Association (No ratings).	Protection nendation, . These values are ines or published the National Fire		ociation (for HMIS			
Label Recommendation: Label Category: ENGINE 0	OIL 1 – ENG1					
Revision Statement: This the following sections of Sheet 2, 3, 4, 7, 8, 10, 11,	this Safety Data					
TLV – Threshold Limit Val	ue	_	TWA – Time Weighted	d Average		
STEL – Short-term Exposu	ıre Limit		PEL – Permissible Expo	osure Limit		
GHS – Globally Harmoniz	ed System		CAS – Chemical Abstra	act Service Number		
ACGIH – American Conference of Governmental Industrial Hygienists		ental Industrial	IMO/IMDG – International Maritime Dangerous Goods Code			
API – American Petroleur	m Institute		SDS – Safety Data She	et		
HMIS – Hazardous Materials Information System		stem	NFPA – National Fire Protection Association (USA)			
DOT – Department of Transportation (USA)		NTP – National Toxicology Program (USA)				
IARC – International Agency for Research on Cancer		OSHA – Occupational Safety and Health Administration				
NCEL – New Chemical Exposure Limit		EPA – Environmental F	Protection Agency			
SCBA – Self-Contained Br	eathing Apparatus					
Revision Date: Decembe	r 20, 2016					
Abbreviations that may have been used in this document:						
Prepared according to the 29 CFR 1910.1200 (2012) by Parman Energy						

Parman Energy makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the use's responsibility to determine the safety, toxicity, and suitability of his own use, handling, and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Parman Energy as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Parman Energy assume liability arising out of the use by others of this product referred to herein. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

Product (s) manufactured in the USA.